





## **Product Identification**

879119

EAQUA URINAL BATT

## **Definition and Application**

• Infrared sensor fluxometer for all type of walls. Connected by battery

## **Technical Features**

- Touch-free, electronically controlled urinal flush valve for concealed installation
- Brushed stainless-steel front plate
- Double infrared sensors (with automatic setting feature)
- Dynamic sensor: constantly adjusts the optimum range
- Temporary-off (cleaning) and short-on (manual flush) activate with touch
- Flush time and sensor sensitivity adjustable with touch
- 24- or 48-hour hygienic flush and pre-flush activate with touch
- 6V Lithium CRP 2 (standard life time up to 4 years)
- Dimensions: 139 X 119mm
- Vandal resistant
- Should be exist a minimum distance between the urinal to the wall of 1 meter
- Required pre-installation of urinal concealed (cod- 879123)

## **Technical Sheet**

**EAQUA** Urinal



Compatiblity	
	Urinal Sanitarblock and Eco Urinal
Warranty	For the terms of warranty please visit <u>www.oli-world.com</u>
Observations	<ul> <li>The fluxometer has to be installed before closing the wall</li> <li>There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site <a href="https://www.oli-world.com">www.oli-world.com</a></li> </ul>