



(dimensions in millimeters)

Product Identification

152966

- Expert Plus Mechanic OLIpure

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications.
- Top or front activation/access
- Flush cistern with interior cleaning system for WC pan

Technical Features

- Dual flush in-wall cistern compatible with dual flush actuators (Narrow and Glam) 6/3 litres (adjustable to 4/2 and 7/3)
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene cistern highly resistable and inalterable to thermal stress
- Lower/under bench installation possibility
- Other versions compliant with: WRAS/SAI-WATWERMARK/SINTEF/NF/BELGAQUA standards
- EN 14055 marking CL1
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

OLIpure System

- Simple refilling system through a control plate of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) *
- Storage capacity:450ml

Accessories

- 1 Discharge pipe 315mm
- 1 Seal for discharge pipe ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Protection pipe ø 45
- 1 WC connection pipe ø45 x 180

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com

Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)
cp* is a unit of measure of viscosity, it reads "centipoise"