



Product Identification

079207

- ELECTRA I Polished chrome zamac

Definition and Application

- Switch (not included) or mechanic control plate to OLI in-wall cistern

Technical Features

- Single flush
- Activation by switch (not included) or mechanical;
- Actuation force <20N
- Dimensions: 243 X 163 mm;
- 17mm thickness
- Electric power connection with pre-installation needed (adapter 230v/120v not included)
- Connecting cable (4000mm) to the switch included
- Polished chrome Zamac material
- Vandal-Proof

Nominal Data

- Voltage supply: 12Vdc
- Power Frequency: dc
- Current consumption: 400mA max
- of protection against the penetration of solid and liquid bodies: IP67
- Environmental conditions during transport and storage:
 - Temperature: -20 / +70°C
 - Relative Humidity: 5 / 95%
 - Pressure: 500 – 1060 hPa
- Environmental working conditions:
 - Temperature: 0 / 40°C
 - Relative Humidity: 5 / 95%
 - Pressure: 500 – 1060 hPa

Accessories

- 2 Fast Fit fixation screws
- 1 Connecting cable
- 1 key for vandal resistant

Compatible Cisterns

- OLI74 PLUS electronic
- OLI120 PLUS electronic

Warranty

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com