



### Product Identification

079205

- Electra II Control Plate

### Definition and Application

- Infrared sensor control plate to OLI in-wall cisterns

### Technical Features

- Dual flush (<60s half flush; >60s full flush)
- Infrared sensor actuation
- Flushes are activated when the user moves away;
- Automatic pre-cleaning
- Polished chrome Zamac material
- Dimensions: 243 X 163 mm;
- 14mm thickness
- Electric power connection with pre-installation needed (adapter 230v/120v not included)
- Vandal-Proof
- Self-discharge in each 24 hours

#### **Nominal Data**

- Voltage supply: 12Vdc
- Power Frequency: dc
- Current consumption: 400mA max
- of protection against the penetration of solid and liquid bodies: IP67
- Environmental conditions during transport and storage:
  - Temperature: -20 / +70°C
  - Relative Humidity: 5 / 95%
  - Pressure: 500 – 1060 hPa
- Environmental working conditions:
  - Temperature: 0 / 40°C
  - Relative Humidity: 5 / 95%
  - Pressure: 500 – 1060 hPa

#### **Accessories**

- 2 Fast Fit actuation screws

### **Compatible Cisterns**

- OLI74 Plus electronic

### **Warranty**

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid.

### **Observations**

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)