



### **Product Identification**

**079205**

- ELECTRA II Polished chrome zamac

### **Definition and Application**

- Infrared sensor control plate to OLI in-wall cisterns

### **Technical Features**

- Dual flush (<60s half flush; >60s full flush)
- Infrared sensor actuation
- Flushes are activated when the user moves away;
- Polished chrome Zamac material
- Dimensions: 243 X 163 mm;
- 14mm thickness
- Electric power connection with pre-installation needed (adapter 230v/120v not included)
- Vandal-Proof
- 

#### **Nominal Data**

- Voltage supply: 12Vdc
- Power Frequency: dc
- Current consumption: 400mA max
- of protection against the penetration of solid and liquid bodies: IP67
- Environmental conditions during transport and storage:
  - Temperature: -20 / +70°C
  - Relative Humidity: 5 / 95%
  - Pressure: 500 – 1060 hPa
- Environmental working conditions:
  - Temperature: 0 / 40°C
  - Relative Humidity: 5 / 95%
  - Pressure: 500 – 1060 hPa

**Accessories**

- 2 Fast Fit fixation screws
- 1 key for vandal resistant
- 1 connection cable for transformer

**Compatible Cisterns**

- OLI74 PLUS electronic
- OLI120 PLUS electronic

**Warranty**

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

**Observations**

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)