



Product Identification

079206

- Electra III Control Plate

Definition and Application

- Infrared sensor or mechanic control plate to OLI in-wall cisterns

Technical Features

- Dual flush (<60s half flush; >60s full flush)
- Infrared sensor or mechanical actuation;
- Flushes are activated when the user moves away;
- Possibility of mechanic actuation in case of failure of electricity
- Automatic pre-cleaning
- Polished chrome Zamac material
- Dimensions: 243 X 163 mm;
- 14mm thickness
- Electric power connection with pre-installation needed (adapter 230v/120v not included)
- Vandal-Proof
- Self-discharge in each 24 hours

Nominal Data

- Voltage supply: 12Vdc
- Power Frequency: dc
- Current consumption: 400mA max
- of protection against the penetration of solid and liquid bodies: IP67
- Environmental conditions during transport and storage:
 - Temperature: -20 / +70°C
 - Relative Humidity: 5 / 95%
 - Pressure: 500 – 1060 hPa
- Environmental working conditions:
 - Temperature: 0 / 40°C
 - Relative Humidity: 5 / 95%
 - Pressure: 500 – 1060 hPa

Accessories

- 2 Fast Fit actuation screws

Compatible Cisterns

- OLI74 Plus electronic

Warranty

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid.

Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com