



## **Product Identification**

**037172**

- QUADRA PLUS Pneumatic

## **Definition and Application**

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications

## **Technical Features**

- Dual flush of 6/3 in-wall cistern compatible with either dual or single flush actuators 6/3 litres (adjustable to 7/3)
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- 187mm thickness
- 270mm reduced width
- Pneumatic actuation
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: NF standards
- EN 14055 marking CL1
- Supplied with anti-condensation lining
- Possibility to put pneumatic actuation 2,5 meters from the cistern

Millimetres measures

#### Accessories

- 1 Discharge pipe 315mm
- 1 Connection pipe ø45
- 1 Seal for discharge pipe ø 40/45
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 WC connection pipe ø45
- 2 fixing plastic links

### **Warranty**

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

### **Observations**

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)