
Technical Sheet

OLI120 Plus Pneumatic Block







Product Identification

154076

OLI120 PLUS Pneumatic Block

Definition and Application

- Pre-assembled structure for setting in masonry walls, to installation of wall-hung sanitary appliances
- Compatible with all wall-hung WC pans

Technical Features

Millimetres measures

Structure

• Metal, tubular painted corrosion resistant

Cistern

- Dual flush in-wall cistern compatible with either dual or single flush actuators 6/3 litres (adjustable to 4/2 and 7/3)
- 144mm thickness
- Pneumatic actuation
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- EN 14055 marking CL1
- Other versions compliant with: WRAS/NF/KIWA/BELGAQUA standards
- Supplied with robust Anti-condensation lining

Accessories

- 1 Flush pipe ø90 x 250
- 1 Seal for flush pipe ø 125
- 1 Connecting pipe ø 45 x 180
- 1 Pan rubber seal ø 45
- 1 Protective box
- 1 G ¹/₂" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend ø 90 / 90 L230
- 1 Outlet bend and ø90/110 adaptor
- 1 Protection pipe Ø90

Fixing accessories for wall structure:

- 3 Galvanized screws M8x70
- 3 Galvanized washers M8 DIN 9021
- 3 Bushing M8

Fixing accessories for toilet bowl mounting on the structure:

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Nuts M12
- 2 Washers ø 34

Warranty

For the terms of warranty please visit <u>www.oli-world.com</u>

Observations

 There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site <u>www.oli-world.com</u>

Millimetres measures