
Technical Sheet

Glassy







Product Identification

878849	GLASSY White
878850	GLASSY Black
878703	GLASSY Red
878702	GLASSY Anthracite
878700	GLASSY Gold
878701	GLASSY Taupe

Definition and Application

Control plate in tempered glass with multiple colours available, dual flush, available for Hydroboost or AC system

Operation

No-touch activation through capacitive sensors with led signs

Sensor

- Protection degree of the sensor: IP67;
- Electronic connectors anti-error and waterproof: IP67;
- Adjustable detection capacity

Technical Features

- Dual flush which allows water saving.
- Actuation through capacitive sensors with LED signs (multiple colours available).
- Gull-Wing opening system which prevents damages to the control plate in actions of installation and maintenance.
- Hygienic and easy to clean
- Waterproof connectors
- Anti-error electronic connections

Technical Sheet

Glassy

ÜLI

Compatible Cisterns

- OLI74 Plus cap Hydroboost or OLI74 Plus cap AC
- OLI120 Plus cap Hydroboost or OLI120 Plus cap AC

Accessories

- Two fixing screws.
- 1 servomotor

Advices

- The installation should be done according to the installation instructions
- Claims arising from improper treatment with acids, chemicals or abrasives are not accepted

Warranty

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

• There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com