



Product Identification

878631	QR-TOTAL Black no-touch cap AC hung wc
878633	QR-TOTAL White no-touch cap AC hung wc

Definition and Application

- Sanitary module designed for application in front of the masonry wall and the best option for a quick renovation bathrooms or new sanitary installations
- Equipped with OLI74 Plus with activation “no-touch” through capacitive sensors.
- Compatible with hung wc pan

Technical Features

Millimetres measures

Structure

- One piece, painted stainless steel lateral frame, black or white
- Four external water entry positions or internal
- 6mm tempered glass front panel (split in two parts)
- Euro Sanitarblock S90
- Metal with 1,5mm thickness, corrosion resistant
- Depth adjustable bend
- Tested for 400kg load

Cistern

- Dual flush 6/3 litres
- Electronic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- EN 14055
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

Sensor

- Operating temperature 0 – 70°C
- Degree of sensor protection: IP67
- Electronic connectors anti-error and waterproof: IP66
- Detection capacity - about 20mm
LED signs

Accessories

- 1 Discharge pipe Ø 90 x 300
- 1 Seal for discharge pipe Ø 125
- 1 Connecting pipe Ø 45 x 180
- 1 Pan rubber seal Ø 45
- 1 Flush bend Ø 90 / 90 L230
- 1 Flexible hose ½" / ½", 250mm
- 1 Adaptor Ø90/110
- 1 Connection 3/8
- 8 Lateral fixations
- 1 Transformer 100-240 6V with cable 2.7M

Fixing the structure to the floor

- 4 Bushing for metal structure
- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021

Warranty

- Ten (10) years warranty for the cistern and the structure, according to the general selling terms, starting from the purchase date of the product.
- Two (2) years warranty for lateral frame, front panel and electronic components according to the general selling terms, starting from the purchase date of the product
- If the product is not correctly installed the warranty is not valid

Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com