



## **Product Identification**

<b>878630</b>	QR-TOTAL Black no-touch cap AC floor
<b>878632</b>	QR-TOTAL White no-touch cap AC floor

## **Definition and Application**

- Sanitary module designed for application in front of the masonry wall and the best option for a quick renovation bathrooms or new sanitary installations
- Equipped with OLI74 Plus with activation “no-touch” through capacitive sensors.
- Compatible with floor wc pan

## **Technical Features**

### **Structure**

- One piece, painted stainless steel lateral frame, black or white
- Four external water entry positions or internal
- 6mm tempered glass front panel (split in two parts) One piece, painted stainless steel lateral frame,
- Metal with 1,5mm thickness, corrosion resistant

#### **Cistern**

- Dual flush 6/3 litres
- Electronic actuation
- Working pressure from 0,1 to 16 bar
- Dedicated regulator for 6L/min filling flow rate
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- EN 14055
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

#### **Sensor**

- Operating temperature 0 – 70°C
- Degree of sensor protection: IP67
- Electronic connectors anti-error and waterproof: IP66
- Detection capacity - about 20mm
- LED signs

#### **Accessories**

- 1 Discharge pipe ø 56 x 200
- 1 Connection pipe ø 45 x 180
- 1 Pan rubber seal ø 45
- 1 Flexible outlet bend ø 90 e ø 90/110 (220mm a 570mm)
- 1 Flexible hose ½ " / ½ ", 250mm
- 1 Connection 3/8
- 8 Lateral fixations
- 1 Battery wall charger with 3m cable extension

#### **Fixing the structure to the floor**

- 4 Bushing for metal structure
- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021

### **Warranty**

- Ten (10) years warranty for the cistern and the structure, according to the general selling terms, starting from the purchase date of the product.
- Two (2) years warranty for lateral frame, front panel and electronic components according to the general selling terms, starting from the purchase date of the product
- If the product is not correctly installed the warranty is not valid

### **Observations**

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)