



Product Identification

216247

- OLI74 Plus Mechanic 4/2 Free Standing

Definition and Application

- Preassembled structure to be secured to the floor only for the installation of wall-hung pans inside light walls
- Compatible with all wall-hung WC pans

Technical Features

Structure

- In painted tubular corrosion resistant
- Height adjustable from 0 to 150mm
- Depth adjustable outlet bend
- Tested for 400kg load

Cistern

- Dual flush in-wall cistern compatible with either dual or single flush actuators 4/2 litres
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: WRAS/SAI-Watermark/UPC/KIWA standards
- EN 14055 marking CL1
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements
-

Accessories

- 1 Discharge pipe ø 90 x 250
- 1 Seal for discharge pipe ø 125
- 1 Connecting pipe ø 45 x 180
- 1 Pan rubber seal ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend ø 90 / 90 L230
- 1 Adaptor ø 90 / 90/110
- 1 Protection pipe Ø90
- 1 Protection pipe Ø45

Fixing accessories for wall structure:

- 4 Bushing for metal structure

Fixing accessories for toilet bowl mounting on the structure:

- 2 Threaded rods M12
- 2 Nuts M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Washers Zn ø 34

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com