



### Product identification

152974  
101768

- Kit OLIpure In-wall flush cisterns
- Kit OLIpure ceramic cisterns

### Definition and Application

- Delayed refilling side inlet valve for cisterns with 3/8" brass connection with refill
- Interior cleaning system of the cistern (OLIpure)

### **Technical Features**

#### **Inlet Valve**

- Delayed refilling (it starts after outlet valve is in closed position)
- Side connection
- Reduced dimensions
- Silent valve class 1 NF certified
- Anti-backflow function
- Counter pressure system

#### **Hydraulic operating properties**

- Dynamic Pressure: 0.1 – 14 bar
- Static pressure: 20 bar

#### **OLIpure System**

- Simple filling system by a small gap on the side of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) \*
- Storage capacity:450ml

Millimetres measures

- Closed circuit: no mixing with the water inside the tank.

## Accessories

- Refill connection pipe 350mm
- Outlet valve connection pipe 130mm
- Liquid sanitizer 450ml

## Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

## Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)

\*Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)

cp\* is a unit of measure of viscosity, it reads "centipoise"